

TABLE B.

Industrial coating alternative Sioo:x Wood Protector for Burnblock FR impregnated:

Name of coating system	Coating codes	Coating system and tested values and test references
Sioo:X Wood Protector coating alternatives, classification Species: Spruce, Larch, Pine, Western Red Cedar, Frake, Ayous, Ash and Douglas Fir B-s1,d0, thickness 19 – 42 mm, over 42 mm B-s2,d0 Testing references: - Classification PCA10812 and PCA10648A / DBI - Indicative test (coating, 19 mm) PFA 12076A / DBI		
Sioo:x Wood Protector Colour alternatives: - Mid Grey - Light Grey - Oyster Grey - Almond Brown	Sioo:x primer wood protector Sioo:x surface protector	Surface planed or fine sawn/paint-cut or fine-brushed Coated industrially after kiln drying with: Primer coating - 2 layers of primer: SiOO:X Primer Wood Protector Industry - total maximum amount applied wet 225 g/m ² Top coating - 1 layer of top coating: SiOO:X Surface Protector Industry - maximum amount applied wet 115 g/m ² Coating conditions and recommendations: According to Sioo Wood Protection instructions
Sioo:X Wood Protector coating alternatives, classification Thermally modified species: Thermo Pine, Thermo Ash, Thermo Ayous, Thermo Spruce, Thermo Frake, Thermo Tulipwood and Thermo Radiata Pine B-s1,d0, thickness 19 – 42 mm, over 42 mm B-s2,d0 Thermally modified species: Thermo Poplar, B-s2,d0, thickness 19 – 42 mm, over 42 mm B-s3,d0 Testing references: - Classification PCA10812 and PCA10648A / DBI - Indicative test (coating, 19 mm) PFA PFA 12076B / DBI		
Sioo:x Wood Protector Colour alternatives: - Mid Grey - Light Grey - Oyster Grey - Almond Brown	Sioo:x primer wood protector Sioo:x surface protector	Surface planed or fine sawn/paint-cut or fine-brushed Coated industrially after kiln drying with: Primer coating - 2 layers of primer: SiOO:X Primer Wood Protector Industry - total maximum amount applied wet 270 g/m ² Top coating - 1 layer of top coating: SiOO:X Surface Protector Industry - maximum amount applied wet 115 g/m ² Coating conditions and recommendations: According to Sioo Wood Protection instructions